

DIGITAL SIGNAGE

SpyeAgent "S"



Introducing the *SpyeAgent* "S". Spyeworks digital signage engine upgraded with additional horsepower (Intel Turbo-boost technology), performance characteristics, and features - including a HD TV capture card and an optimized chipset to handle the increased demands of streaming HD content. The "S" has noticeable physical differences from the the standard *SpyeAgent*, namely a slightly larger form factor, heavier heat sink, and an full size expansion slot.

SP

Player and Network Agent software imbedded. SpyeCreator and SpyeManager software included with first agent.

Benefits

- · Optimized for Streaming HD content
- Wireless networking hardware included
- Embedded software allows offsite support and monitoring
- · Dual Live display outputs
- HD Capture card or 3G wireless card
- · DIN-rail, Rack, and VESA mount kits
- 1 year warranty/support

Specifications

Platform	
Form Factor	Smart Fanless System
Processor	Intel i5 Processor
Memory	
Installed Memory	4GB DDR2 800 SO-DIMM
Max Memory	8GB (4GB Module x 2)
Storage	
HDD	160 GB
Video	
Controller	Intel HD Graphics
Hardware	
Watchdog Timer	Yes (1~255 level)
OS	
Operating System	Windows Seven 64 bit Embedded

I/O

1/0	
COM Parts	RS-232 x 2
USB 2.0	4 (External x 4)
VGA	1 (2048 x 1536 / 75Hz)
DVI-D	1 (1920 x 1080)
LAN	RJ45 GbE x 2
Audio	Stereo Line Out (RCA L/R)
DC-in Connector	Phoenix Contact Screw Lock
Wireless	Wi-Fi Mini-PCle Mini Card SMA + Antenna

Dimensions

W x H x D (mm)	276.5(W) x 65(H) x 190(D)
W x H x D (Inch)	10.88"(W) x 2.55"(H) x 7.48"(D)
Devuer	
Power	
Input (Mode)	DC + 9-30V (ATX Mode)
AC Adapter	AC Adapter C: 60W (+24v)
	Phoenix Contact Screw Lock